

Pureflex[™] Mega Series PF-600AB

Absolute* Pleated Polypropylene FILTER CARTRIDGES

Pureflex[™] Mega Series PF-600AB Cartridges are uniquely designed large diameter (6- and 6.5-inch) cartridges that maximize service life, and optimize efficiency.

APPLICATIONS

• Chemical

• Magnetic Media

• Cosmetic

Medical

• Electronic

• Pharmaceutical

• Food and Beverage

Photographic

Ink

• Pre-filter for RO Systems

CARTRIDGE OPERATION

Pureflex™ Mega Series PF-600AB are large diameter, coreless, single open end cartridges with an inside-out flow pattern. These 6- and 6.5-inch diameter cartridges allow the use of significantly smaller housings and fewer filters. The cartridges are constructed of FDA-listed materials and a thermal-bonding process is used to seal the media, core, cage, and endcaps. This adhesive-free process ensures bypass-free filtration.

FEATURES

- Available in 6- and 6.5-inch diameters with nylon endcaps
- Efficiency ratings of 99.98% (Beta 5000) at stated micron size
- Long cartridge life, 20-40 times fewer element change-outs than comparable standard diameter cartridges
- Inside-out flow—all debris remains within filter
- Coreless construction minimizes waste disposal
- High dirt-holding capacity
- 100% polypropylene media runs full length of cartridge
- Single-piece cage and core construction
- Silicone or Buna-N® gaskets and o-rings
- Smaller filter vessel possible
- Chemically compatible in most applications
- High-purity filtration for a wide range of applications

Custom housings are available for these cartridges. Contact our technical support team for more details.

SPECIFICATIONS


Component	Material/Value
Fiber Media	Polypropylene
Maximum Temperature Rating	180°F (82.2°C)
Maximum Differential Pressure	50 PSID



Pureflex[™] Mega Series PF-600AB Filter Cartridges

ORDERING INFORMATION

Custom configurations available; please contact Customer Service.



DIMENSIONS AND CONSTRUCTION

Pureflex™ Mega Series PF-600AB			
Diameter (Inches)		6	6.5
Length (Inches)	5		
	9.7		
	10		
	20	•	
	30		
	39		
	40	•	•
	60	•	
Hard Cage			
Soft Cage		•	•
Center Core		_	SS
Endcap		N	N
Outer Sleeve		P, SS	Р
Endcap Style	D0E	•	
	SOE		
	S2		
	F2		
	S6		•
	F6		•
	S3		
	S4		
Seal		В	В

Cartridge Availability Key	
P	Polypropylene
N	Nylon
SS	304 Stainless Steel
S6	226 Flat
DOE	Double Open End
В	Buna-N®



502 Indiana Avenue, Sheboygan, WI 53082-1047 800.869.0325 574.278.7161 FAX 574.278.7115 support@pentairindustrial.com www.pentairindustrial.com

©2008 Pentair Filtration Printed in USA AP08 380062